


DC/DC Converter

TMR 3WIE Series, 3 Watt

Not recommended for new designs

- Wide 4:1 input voltage range
- Compact SIP-8 package
- Cost optimized design
- Temperature range -40°C to $+85^{\circ}\text{C}$
- I/O isolation 1600 VDC
- Remote On/Off control
- 3-year product warranty



UL 62368-1 IEC 62368-1

The TMR 3WIE series is a family of isolated 3 W DC/DC converter modules with regulated output, featuring wide 4:1 input voltage ranges. The product comes in a compact SIP-8 plastic package with small footprint occupying only 2.0 cm² (0.3 square inch) of board space.

An excellent efficiency allows -40°C to $+85^{\circ}\text{C}$ operation temperature. Further features include remote On/Off control and continuous short circuit protection. The compact dimensions and cost optimized design make this converters an ideal solution for applications in communication equipment, instrumentation and industrial electronics.

Models						
Order Code	Input Voltage Range	Output 1		Output 2		Efficiency typ.
		Vnom	I _{max}	Vnom	I _{max}	
TMR 3-1210WIE *	4.5 - 18 VDC (12 VDC nom.)	3.3 VDC	700 mA			74 %
TMR 3-1211WIE *		5 VDC	600 mA			78 %
TMR 3-1212WIE *		12 VDC	250 mA			80 %
TMR 3-1213WIE *		15 VDC	200 mA			80 %
TMR 3-1221WIE *		+5 VDC	300 mA	-5 VDC	300 mA	80 %
TMR 3-1222WIE *		+12 VDC	125 mA	-12 VDC	125 mA	80 %
TMR 3-1223WIE *		+15 VDC	100 mA	-15 VDC	100 mA	80 %
TMR 3-2410WIE *	9 - 36 VDC (24 VDC nom.)	3.3 VDC	700 mA			75 %
TMR 3-2411WIE *		5 VDC	600 mA			80 %
TMR 3-2412WIE *		12 VDC	250 mA			81 %
TMR 3-2413WIE *		15 VDC	200 mA			81 %
TMR 3-2421WIE *		+5 VDC	300 mA	-5 VDC	300 mA	79 %
TMR 3-2422WIE *		+12 VDC	125 mA	-12 VDC	125 mA	80 %
TMR 3-2423WIE *		+15 VDC	100 mA	-15 VDC	100 mA	81 %
TMR 3-4810WIE *	18 - 75 VDC (48 VDC nom.)	3.3 VDC	700 mA			74 %
TMR 3-4811WIE *		5 VDC	600 mA			79 %
TMR 3-4812WIE *		12 VDC	250 mA			79 %
TMR 3-4813WIE *		15 VDC	200 mA			79 %
TMR 3-4821WIE *		+5 VDC	300 mA	-5 VDC	300 mA	79 %
TMR 3-4822WIE *		+12 VDC	125 mA	-12 VDC	125 mA	79 %
TMR 3-4823WIE *		+15 VDC	100 mA	-15 VDC	100 mA	80 %

Note * Not recommended for new designs

Input Specifications

Input Current	- At no load	12 Vin models: 60 mA typ. 24 Vin models: 25 mA typ. 48 Vin models: 15 mA typ.
	- At full load	12 Vin models: 300 mA typ. 24 Vin models: 150 mA typ. 48 Vin models: 75 mA typ.
Surge Voltage		12 Vin models: 25 VDC max. (1 s max.) 24 Vin models: 50 VDC max. (1 s max.) 48 Vin models: 100 VDC max. (1 s max.)
Under Voltage Lockout		12 Vin models: 4 VDC max. 24 Vin models: 8 VDC max. 48 Vin models: 16 VDC max.
Recommended Input Fuse		12 Vin models: 1'500 mA (slow blow) 24 Vin models: 700 mA (slow blow) 48 Vin models: 350 mA (slow blow) (The need of an external fuse has to be assessed in the final application.)
Input Filter		Internal Capacitor
Short Circuit Input Power		2.5 W max.

Output Specifications

Voltage Set Accuracy		±1% max.
Regulation	- Input Variation (Vmin - Vmax)	single output models: 0.5% max. dual output models: 0.5% max.
	- Load Variation (25 - 100%)	single output models: 1% max. dual output models: 1% max. (Output 1) 1% max. (Output 2)
	- Voltage Balance (symmetrical load)	dual output models: 2% max.
Ripple and Noise	- 20 MHz Bandwidth	75 mVp-p max.
Capacitive Load	- single output	3.3 Vout models: 1'760 µF max. 5 Vout models: 1'000 µF max. 12 Vout models: 170 µF max. 15 Vout models: 110 µF max.
	- dual output	5 / -5 Vout models: 470 / 470 µF max. 12 / -12 Vout models: 100 / 100 µF max. 15 / -15 Vout models: 47 / 47 µF max.
Minimum Load		25 % of Iout max. (Operation at lower load will not damage the converter, but it may not meet all specifications)
Temperature Coefficient		±0.02 %/K max.
Short Circuit Protection		Automatic recovery
Overload Protection		Foldback Mode
Output Current Limitation		110% min. of Iout max. 140% typ. of Iout max.
Transient Response	- Response Deviation	5% max. (25% Load Step)
	- Response Time	300 µs typ. / 500 µs max. (25% Load Step)

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

Safety Specifications

Standards - IT / Multimedia Equipment

CSA-C22.2, No. 60950-1

EN 60950-1

EN 62368-1

IEC 60950-1

IEC 62368-1

UL 60950-1

UL 62368-1

- Certification Documents

www.tracopower.com/overview/tmr3wie

EMC Specifications

EMI (Emissions) - Conducted Emissions

EN 55032 class A (with external filter)

FCC 47 Part 15 class A (with external filter)

- Radiated Emissions

EN 55032 class A (with external filter)

FCC 47 Part 15 class A (with external filter)

External filter proposal: www.tracopower.com/overview/tmr3wie

General Specifications

Relative Humidity 95% max. (non condensing)

Temperature Ranges - Operating Temperature

-40°C to +85°C

- Case Temperature

+105°C max.

- Storage Temperature

-55°C to +125°C

Power Derating - High Temperature

3.3 %/K above 70°C

See application note: www.tracopower.com/overview/tmr3wie

Cooling System

Natural convection (20 LFM)

Remote Control - Voltage Controlled Remote (passive = on)

On: < 0.6 VDC or open circuit

Off: 2.7 to 15 VDC

Refers to 'Remote' and '-Vin' Pin

- Off Idle Input Current

2.5 mA max.

- Remote Pin Input Current

-1.0 to 1.0 mA

Altitude During Operation

6'000 m max.

Switching Frequency

350 kHz typ. (PFM)

Insulation System

Functional Insulation

Isolation Test Voltage - Input to Output, 60 s

1'600 VDC

- Input to Output, 1 s

1'920 VDC

Isolation Resistance - Input to Output, 500 VDC

1'000 MΩ min.

Isolation Capacitance - Input to Output, 100 kHz, 1 V

200 pF typ.

Reliability - Calculated MTBF

900'000 h (MIL-HDBK-217F, ground benign)

Washing Process

According to Cleaning Guideline

www.tracopower.com/info/cleaning.pdf

Housing Material

Non-conductive Plastic (UL 94 V-0 rated)

Potting Material

Epoxy (UL 94 V-0 rated)

Pin Material

Nickel-Iron (Alloy 42)

Pin Foundation Plating

Nickel (1 μm min.)

Pin Surface Plating

Tin (3 - 5 μm), matte

Housing Type

Plastic Case

Mounting Type

PCB Mount

Connection Type

THD (Through-Hole Device)

Footprint Type

SIP8

Soldering Profile

Lead-Free Wave Soldering

260°C / 6 s max.

Weight

4.8 g

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

Environmental Compliance - REACH Declaration

www.tracopower.com/info/reach-declaration.pdf

- RoHS Declaration

REACH SVHC list compliant

REACH Annex XVII compliant

www.tracopower.com/info/rohs-declaration.pdf

Exemptions: 7(a)

(RoHS exemptions refer to the component concentration only, not to the overall concentration in the product (O5A rule).)

- SCIP Reference Number

ba78b077-d7c0-469e-a81b-129de38ae165

Additional Information

Supporting Documents

www.tracopower.com/overview/tmr3wie




Frequently Asked Questions

www.tracopower.com/glossary-faq

Glossary

www.tracopower.com/info/glossary.pdf

Outline Dimensions



Dimensions in [mm], () = Inch

Tolerances: ± 0.5 (± 0.02)

Pin pitch tolerances: ± 0.25 (± 0.01)

Pinout

Pin	Single Output	Dual Output
1	-Vin (GND)	-Vin (GND)
2	+Vin (Vcc)	+Vin (Vcc)
3	Remote	Remote
5	NC	NC
6	+Vout	+Vout
7	-Vout	Common
8	NC	-Vout

NC: Not connected