

Industrial Power Supplies

- Slim profile, for DIN-rail mounting
- Alternative side-mounting for flat panels
- High power factor by active power correction
- Very high efficiency up to 94.0%
- Back power immunity
- 150% peak current for 4 sec.
- Operating temperature range: -40°C to +70°C max.
- Adjustable output voltage
- DC-OK indicator
- Short circuit and overload protection
- Class I, division 2 approval and ATEX certification for EX-models
- 5-year product warranty for EX-models

TIB 120 Series, 120 Watt



Other output power of same series:

This generation of DIN-rail power supplies combines the most efficient circuit topology with optimized cost/performance ratio for industrial environments and for electrical control cabinets.

They have a very high efficiency of up to 94.0% which allows a very slim package design. The output voltage is adjustable from -2% to +17%. The case offers the potentially useful feature to fix the DIN-rail clip to the side wall for the mounting inside flat panels. Over a period of minimum 4 seconds they can operate with a boost power of 150%. The boost power facilitates the activation of stepper motors, solenoids or actuators. The units operate with a high power factor of up to 97% by active power factor correction which also keeps the input inrush current low. The TIB series are also available with other nominal power of 80, 240 or 480 Watt (+50% boost power). They come with the safety standard approvals for IEC/EN 60950-1, UL 60950-1 and UL 508.

Models				
Order Code	Output Power (max.)	Output Voltage nom. (adjustable)	Output Current (max.)	Efficiency (typ.)
TIB 120-112	120 W	12 VDC (11.8–15.0)	10 A	94.0 %
TIB 120-112EX				
TIB 120-124	120 W	24 VDC (23.5–28.0)	5 A	94.0 %
TIB 120-124EX				
TIB 120-148	120 W	48 VDC (47.0–56.0)	2.5 A	94.0 %
TIB 120-148EX				

Input Specifications

Input voltage	– nominal ranges – effective ranges	100 – 240 VAC 85 – 264 VAC (below 90 VAC a derating of 3%/V is required)
Input voltage frequency		45 – 65 Hz
Standby power consumption		2.2/2.2 W (115/230 VAC)
Power Factor Correction (PFC)		0.97/0.8 (115/230 VAC)
Harmonic limits	– acc. EN 61000-3-2	class A, D
Inrush current		15/30A max. (115/230 VAC)

Output Specifications

Output voltage adjustment ¹⁾		12 Vout models: 11.8 – 15.0 V 24 Vout models: 23.5 – 28.0 V 48 Vout models: 47.0 – 56.0 V
Regulation	– Input variation – Load variation (10–90 %)	0.1 % max. 0.5 % max.
Temperature coefficient		0.02 %/K
Hold-up time		20 ms min.
Start-up time		2 s max.
Ripple and Noise (20MHz bandwidth)	12 & 24 Vout models: 48 Vout models:	100 mVp-p max. 200 mVp-p max.
Output overvoltage protection (OVP) ²⁾	12 Vout models: 24 Vout models: 48 Vout models:	16 – 19V 32 – 35V 56 – 60V
Power back immunity ³⁾		< OVP level
Operation	– Nominal operation – Peak power operation – Constant current (cc)	100 % of Iout nom. 105 – 150 % of Iout nom. > 155 % of Iout nom.
Duty cycle ⁴⁾ (for peak and cc mode)	– Threshold – CC or peak operation timer – normal operation / off period	> 105 % 4 s max. (switch off) 10 s typ. (automatic restart after switch off or peak and cc operation timer reset)
Short circuit		Switch off after 4s delay, automatic restart
DC OK signal	– Threshold for Vout – DC ON – DC OFF	12 Vout models: on: > 10.9 V typ., off: < 10.7V typ. 24 Vout models: on: > 22.5 V typ., off: < 21.5 V typ. 48 Vout models: on: > 45 V typ., off: < 43 V typ. relay contact closed, 1 A max., < 100 mOhm (also indicated by green LEDs: front and side) relay contact open, 30 V max.

¹⁾ Output voltage can be adjusted as indicated. However, output power has to be maintained at nominal value. This means the output nominal current has to be reduced in accordance with the increase of output voltage.

²⁾ In case of an internal error a second voltage regulation loop keeps the output voltage at a safe level, the power supply turns off and restarts after typ. 10 seconds.

³⁾ When external voltage is supplied above set output voltage and below OVP threshold, the power supply will function normally without switch off or destruction, even if external voltage is applied continuously.

⁴⁾ In case of overload or short circuit, the unit switches the output voltage off after 4 seconds and tries to restart every typ. 10 seconds.


All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

General Specifications


Operating temperature range		–40°C to +70°C max.		
Derating		2 %/K above +60°C		
Cooling		convection cooling, no internal fan		
Overtemperature protection		switch off at overtemperature		
Humidity (non condensing)		5–95 % rel. H max.		
Altitude during operation		2000 m max.		
Isolation Voltage	– Input/Ouput	4250 VDC		
	– Input/Chassis	1500 VDC		
	– Ouput/Chassis	750 VDC		
Creepage Clearance	– Input/Ouput	8 mm		
	– Input/Chassis	4 mm		
	– Output/Chassis	1.5 mm		
MTBF (acc. to IEC 61709 at 25°C)		> 1'450'000 h		
Safety standards	– Information technology equipment	IEC/EN 60950-1, UL 60950-1 CSA 22.2 No 60950-1-03		
	– Safety low voltage switchgear and controlgear	UL 508		
	– ATEX for hazardous location (EX models only)	EN 60079-0, EN 60079-7, EN 60079-15 (EX II3G Ex ec nC IIC GC)		
	– UL HazLoc (EX models only)	Class I, Division 2		
Electromagnetic compatibility (EMC), Emissions	– Conducted emission input	EN 61000-6-3, EN 61204-3		
	– Radiated RI emission	EN 55032, EN 55011 class B		
		EN 55032, EN 55011 class B		
Electromagnetic compatibility (EMC), Immunity	– Railway applications signalling apparatus	EN 61000-6-2, EN 61204-3		
	– Railway applications rolling stock apparatus	EN 50121-4		
	– Electrostatic discharge (ESD)	EN 50121-3-2		
	– Radiated RF field immunity	IEC/EN 61000-4-2	4 kV/8 kV	criteria A
	– Electrical fast transient / burst immunity	IEC/EN 61000-4-3	10 V/m	criteria A
	– Surge immunity	IEC/EN 61000-4-4	2 kV	criteria B
	– Immunity to conducted RF disturbances	IEC/EN 61000-4-5	1 kV/2 kV	criteria B
	– Power frequency field immunity	IEC/EN 61000-4-6	10 V	criteria A
	– Mains voltage dips and interruptions	IEC/EN 61000-4-8	30 A/m	criteria A
	– Voltage sag immunity	IEC/EN 61000-4-11		criteria B/C
		SEMI F47 (230 VAC)		criteria A
Environment	– Railway applications shock and vibration	according EN 61373		
	– Vibration acc. IEC 60068-2-6-3	3 axis, 2 g sine sweep, 10–55 Hz, 11 okt/min		
	– Shock acc. IEC 60068-2-27	3 axis, 25 g half sine, 11 ms		
Enclosure material	– Chassis	aluminium		
	– Cover	stainless steel		
Mounting	– DIN-rail mounting	for DIN-rails as per EN 50022-35×15/7.5		
Environmental compliance	– Reach	RoHS directive 2011/65/EU		
	– RoHS			
Connection		screw terminals		

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Function Specification




Output Characteristic




Characteristic: Output voltage vs output current for overload conditions until switch off after 4s at nominal input voltages

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Output Characteristic (continued)




Derating: max load vs input voltage



Derating: Load vs ambient temperature

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Outline Dimensions



Alternative side mounting:

